

WHAT IS CLAIMED IS:

1. A terminal device comprising:
a control section for controlling the terminal device;
a first real-time clock which is built in the control section; and
a second real-time clock which is provided outside the control

5 section, wherein:

the control section obtains information from the first real-time clock when the terminal device is in a first operation mode, and
the control section obtains information from the second real-time clock when the terminal device is in a second operation mode.

2. A terminal device as claimed in claim 1, wherein the second real-time clock is directly connected to the control section by a signal line.

3. A terminal device as claimed in claim 1, wherein the second real-time clock is connected to the control section via a functional device.

4. A terminal device as claimed in claim 1, wherein the second real-time clock is built in a functional device which is connected to the control section.

5. A terminal device as claimed in claim 1, wherein the information obtained from the second real-time clock is transferred to the first real-time clock and thereafter the control section obtains the information from the first real-time clock.

6. A terminal device as claimed in claim 5, wherein the information of the first real-time clock is restored by use of the information transferred from the second real-time clock.

10073461-02302

7. A terminal device as claimed in claim 1, wherein the control section and the second real-time clock are powered by different power sources.

8. A terminal device as claimed in claim 1, wherein the information at least includes time information and date information.

9. A terminal device as claimed in claim 1, wherein:

the first operation mode is enabled when the control section is operating normally, and

the second operation mode is enabled when the control section
5 recovered from failure.

10. A terminal device as claimed in claim 1, wherein the control section is implemented by a microcomputer which is built in the terminal device.

11. A method for controlling a real-time clock of a terminal device, comprising the steps of:

a mode judgment step for judging whether the terminal device is in a first operation mode or a second operation mode;

5 a first information obtaining step in which a control section of the terminal device obtains information from a first real-time clock which is built in the control section if the terminal device is in the first operation mode, and

10 a second information obtaining step in which the control section obtains information from a second real-time clock which is provided outside the control section if the terminal device is in the second operation mode.

10073151.021302
20070920 15:09:09

12. A method as claimed in claim 11, wherein the second real-time clock is directly connected to the control section by a signal line.

13. A method as claimed in claim 11, wherein the second real-time clock is connected to the control section via a functional device.

14. A method as claimed in claim 11, wherein the second real-time clock is built in a functional device which is connected to the control section.

15. A method as claimed in claim 11, wherein the information obtained from the second real-time clock is transferred to the first real-time clock and thereafter the control section obtains the information from the first real-time clock.

16. A method as claimed in claim 15, wherein the information of the first real-time clock is restored by use of the information transferred from the second real-time clock.

17. A method as claimed in claim 11, wherein the control section and the second real-time clock are powered by different power sources.

18. A method as claimed in claim 11, wherein the information at least includes time information and date information.

19. A method as claimed in claim 11, wherein:

the first operation mode is enabled when the control section is operating normally, and

the second operation mode is enabled when the control section
5 recovered from failure.

10073161.021302

20. A method as claimed in claim 11, wherein the control section is implemented by a microcomputer which is built in the terminal device.

10073361.021302
20251201 19:55:00